

# **FABRIC GUARD**

# FOR EXTERIOR & INTERIOR SURFACES

A stain and water-repellent nano-formulated solution designed to shield natural fabrics without changing their appearance.



### **FEATURES**



**WATER & OIL RESISTANT** 



**RETAINS BREATHABILITY** 



PRESERVES NATURAL LOOK



PREVENTS SUN-FADING

## **SUBSTRATES**



**NATURAL FABRICS** 



**SUEDE & LEATHERS** 

## PREVENTATIVE MAINTENANCE



**CARPET STAINS** 



**UPHOLSTERY DAMAGE** 



HIGH CLEANING COSTS



## THE NANO-SCIENCE

ARMUS Fabric Guard is a water-based formulation that creates a repelling barrier on the treated surface from the inside out. It prevents oil and water from penetrating and staining surfaces, without changing the natural appearance of the fabric and without applying harsh chemicals. Pat surfaces clean easily with a damp cloth!

## **APPLICATION**

#### SURFACE PREP

• Wipe all surfaces clean of dust & debris.

#### **APPLICATION**

- Shake well before application.
- No dilution is required.
- Apply by using spray, brush, or roller.
- Textiles such as cotton can also be dipped for 5 to 10 minutes.
- The application on leather can be done by polishing Fabric Guard onto the material.
- Before full-scale application, test results in a small area.
- On very absorptive surfaces re-apply within 1 hour.
- Maximum protection is achieved 24 hours post-application.

#### **ESTIMATED CONSUMPTION**

• Up to 300 sq.ft. per gallon, dependent on properties of surface.

SCAN OR CODE TO REAL FULL TECHNICAL DATA SHEET BEFORE APPLYING.

## **SAFETY AND STORAGE**

#### **WARNING:**

- Use in a well-ventilated area.
- Remove and wash contaminated clothing prior to reuse.
- Wear proper protective gear and clothing, eye or face protection prior to application.

#### STORAGE & DISPOSAL

- Store indoors in a closed container. Storage temperature should be between +50°F to 95°F (+10°C to +35°C).
- Protect from frost.
- Disposal of container and material safely according to local laws and regulations.

SCAN OR CODE TO READ FULL SAFETY DATA SHEET BEFORE APPLYING.

