

FLOOR GUARD EXTREME (Part A)

SAFETY DATA SHEET ACCORDING TO USA FEDERAL HAZCOM 012

1. IDENTIFICATION

1.1. Product Identifier

Code:

A-FLOORX-A

Product name

FLOOR GUARD EXTREME (Part A)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

*Self-leveling polyaspartic elastomeric floor coating with high resistance to weathering or UV; Part A base.
For professional use only.*

1.3. Details of the supplier of the safety data sheet

Name

Armus LLC

Full address

137 Grand Street 3rd Floor
New York, NY 10013

Country

United States
Tel. (+1) 917-957-5383

E-mail address of the competent person responsible for the Safety Data Sheet

bill@armussolutions.com

1.4. Emergency telephone number

For urgent inquiries refer to

Tel. (+1) 917-957-5383 United States

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment is given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Specific target organ toxicity – repeated exposure, category 1

Causes damage to organs through prolonged or repeated exposure.
May cause an allergic skin reaction.

Skin sensitization, category 1

Hazard pictograms:



Signal words:

DANGER

Hazard statements:

H372	Causes damage to organs through prolonged or repeated exposure.
H317	May cause an allergic skin reaction.

Precautionary statements:**Prevention:**

P260	Do not breathe fume, mist, or spray.
P280	Wear protective gloves.
P270	Do not eat, drink, or smoke when using this product.
P264	Wash with plenty of soap and water thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.

Response:

P314	Seek medical advice / attention if you feel unwell.
P333+P313	If skin irritation or rash occurs: Seek medical advice / attention immediately.
P302+P352	IF ON SKIN: Wash with plenty of water.
P363	Wash contaminated clothing before reuse.

Storage:**Disposal:**

P501	Dispose of contents or container according to local/national/international regulations
------	--

2.2 Other hazards

This product is classified as hazardous for the environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

Classification and Hazard Statement

Hazardous to the aquatic environment, chronic toxicity, category 3	Harmful to aquatic life with long-lasting effects.
---	--

Hazard statements:

H412	Harmful to aquatic life with long-lasting effects.
------	--

Precautionary statements:**Prevention:**

P273	Avoid release into the environment.
------	-------------------------------------

Response:**Storage:****Disposal:**

P501	Dispose of contents or container according to local/national/international regulations
------	--

2.3 Additional hazards

Contains 4-morpholinecarbaldehyde. May produce an allergic reaction.

3. COMPOSITION / INFORMATION ON INGREDIENTS**3.1. Components**

<i>Chemical Name</i>	<i>CAS-No</i>	<i>EC</i>	<i>INDEX</i>	<i>Conc. %</i>	<i>Classification</i>
Aspartic Acid, N.N'- (methylenedi-4.1-	136210-30-5	429-270-1	607-521-00-8	43.65	Skin sensitization, category 1 H317, Hazardous to the aquatic

Safety Data Sheet

Floor Guard Extreme – A- FLOORX-A
07.25.2023, Version 01.02
Page 2 of 10

cyclohexanediyl) bis-, 1.1',4.4'-tetraethyl ester					environment, chronic toxicity, category 3 H412
Tridymite	15468-32-2	239-487-1	---	5	Specific organ toxicity – repeated exposure, category 1 H372
Cristobalite	14464-46-1	238-455-4	---	5	Specific organ toxicity – repeated exposure, category 1 H372

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. FIRST-AID MEASURES

4.1. Description of first aid measures

GENERAL ADVICE:

Move out of work / application area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.

EYES:

Remove contact lenses.
Keep eyes wide open while rinsing.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical attention.
Continue rinsing eyes during transport to medical facility or for at least 30-60 minutes.

SKIN:

Take off contaminated clothing and shoes immediately.
Wash immediately with plenty of water.
If irritation persists, seek medical advice/attention.
Wash contaminated clothing before using it again.

INHALATION:

Move to fresh air.
In the event of breathing difficulties, seek medical advice/attention immediately.

INGESTION:

Seek medical advice / attention immediately.
Do not induce vomiting without medical advice.
Never give anything by mouth to an unconscious person, unless authorized by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product is unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Not applicable based on available information.

5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing equipment

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder, and water spray.

Unsuitable extinguishing equipment

None in particular.

5.2. Special hazards arising from the substance or mixture

Specific hazards during fire fighting

Do not breathe combustion products.

5.3. Advice for firefighters

General information

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health.
Always wear full fire prevention gear.
Collect extinguishing water to prevent it from draining into the sewer system.

Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

Special protective equipment for fire-fighters

Normal firefighting clothing i.e., fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment, and emergency procedures

Block the leakage.

Wear suitable protective equipment (including personal protective equipment referred to under section 8 of the safety data sheet) to prevent any contamination of skin, eyes, and clothing.

These indications apply for both product users and those involved in emergency procedures.

6.2. Environmental precautions

The product must not enter the sewer system or come into contact with surface water or groundwater.

6.3. Methods and material for containment and cleaning up

Collect the leaked product.

Absorb spilled product with inert absorbent material.

Make sure the leakage site is well-aired.

Contaminated material should be disposed of in compliance with the provisions set forth in section 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet.

Do not eat, drink, or smoke during use.

Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

This product must not enter the sewer system or come into contact with surface water or groundwater.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container.

Store the containers sealed, in a well-ventilated place, away from direct sunlight.

7.3. Specific end use(s)

Refer to section 1.2

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

Regulatory References:

USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2020

CRISTOBALITE						
Threshold Limit Value						
Type	Country	TWA / 8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	Ppm	
OEL	EU	0.1				RESP
TLV-ACGIH	---	0.025				
CAL/OSHA	USA	0.05				RESP

TRIDYMITE						
Threshold Limit Value						
Type	Country	TWA / 8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	Ppm	
CAL/OSHA	USA	0.05				RESP

Legend:

(C) = CEILING
 INHAL = Inhalable Fraction
 RESP = Respirable Fraction
 THORA = Thoracic Fraction

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well-aired through effective local ventilation. Personal protective equipment must comply with current regulations.

<i>Hand Protection</i>	Protect hands with category III work gloves (OSHA 29 CFR 1910.138). The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.
<i>Skin Protection</i>	Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.
<i>Eye Protection</i>	Wear airtight protective goggles (OSHA 29 CFR 1910.133).
<i>Respiratory Protection</i>	If the threshold value (e.g., TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapors of various kinds and/or gases or vapors containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited. If the substance considered is odorless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.
<i>Environmental Exposure Controls</i>	This product must not enter the sewer system or come into contact with surface water or groundwater.

Safety Data Sheet

Floor Guard Extreme – A- FLOORX-A
 07.25.2023, Version 01.02
 Page 5 of 10

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Color	White
Odor	Light
pH	Not applicable
Density	1.2 g/cm ³
Flash point	> 86°F (30°C) @ 1,013 hPa
Initial boiling point	> 392°F (200°C)
Auto-ignition temperature	> 698°F (370°C) @ 1,013 hPa
Viscosity	> 4770 cP @ 68°F (20°C)
Vapor pressure	0.0003 hPa @ 68°F (20°C)
Explosive properties	None
Oxidizing properties	None

10. STABILITY AND REACTIVITY

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However, the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

None based on available information.

10.6. Hazardous decomposition products

None based on available information.

11. TOXICOLOGICAL INFORMATION

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

CRISTOBALITE	The probable carcinogenic risk is related to the presence of quartz.
---------------------	--

Information on likely routes of exposure

CRISTOBALITE	Workers	Inhalation.
---------------------	---------	-------------

Delayed and immediate effects as well as chronic effects from short and long-term exposure

CRISTOBALITE	The crystalline forms of silica are those of more interest to occupational medicine and industrial hygiene, since responsible for diseases of a disabling nature. Exposure to dust containing crystalline silica causes silicosis. Chronic silicosis occurs after
---------------------	---

Safety Data Sheet

a variable period from exposure (latency), progressing even after interruption of exposure, closely related to the extent and duration of exposure (deterministic effects). Over time, this situation tends to worsen, even so far as to cause the death of the person suffering from silicosis. Patients suffering from silicosis are often associated with tuberculosis (silico-tuberculosis), currently widespread in many developing countries. In a more overall perspective, silicosis is to be considered only the initial stage of a disease that has a high risk of progressing and generating more serious complications, such as lung cancer and autoimmune diseases.

Interactive effects

Not classified based on available information.

Acute toxicity

Titanium Dioxide

LD50 (Oral (Rat)) 10,000 mg/kg

Skin corrosion / irritation

Not classified based on available information.

Serious eye damage / irritation

Not classified based on available information.

Respiratory or skin sensitization

Sensitizing for the skin.

Contains:

4-morpholinecarbaldehyde

May produce an allergic reaction.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Carcinogenicity Assessment:

CRISTOBALITE

11464-46-1

ACGIH: A2

IARC: 31

Classified in Group A2 (suspected human carcinogen) by the American Conference for Governmental Industrial Hygienists (ACGIH).

Classified in Group 1 (human carcinogen) by the International Agency for Research on Cancer (IARC).

Reproductive toxicity

Not classified based on available information.

STOT – single exposure

Not classified based on available information.

STOT – repeated exposure

Causes damage to organs.

Aspiration toxicity / hazard

Not classified based on available information.

12. ECOLOGICAL INFORMATION

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it has negative effects on aquatic environment.

12.1. Toxicity

None based on available information.

Safety Data Sheet

Floor Guard Extreme – A- FLOORX-A

07.25.2023, Version 01.02

Page 7 of 10

12.2. Persistence and degradability

Titanium Dioxide

Solubility in Water < 0.001 mg/liter

12.3. Bioaccumulative potential

None based on available information.

12.4. Mobility in soil

None based on available information.

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any Persistent, Bioaccumulative and Toxic (PBT) or very Persistent and very Bio-accumulative (vPvB) in percentages greater than 0.1%.

13. DISPOSAL CONSIDERATIONS

Disposal methods

<i>Waste from residues</i>	Reuse, when possible. Unused product should be considered special non-hazardous waste. Disposal must be performed through an authorized waste management firm, in compliance with local, national, and international regulations.
<i>Contaminated Packaging</i>	Contaminated packaging must be recovered or disposed of in compliance with all waste management regulations.

14. TRANSPORTATION INFORMATION

This product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID) of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

15. REGULATORY INFORMATION

U.S. Federal Regulations

<i>TSCA</i>	All components of this product are listed on US Toxic Substances Control Act (TSCA) Inventory considered as "existing" chemical substances in U.S. commerce.
<i>Clean Air Act Sections 112(b), including 602 Class I Substances, 602 Class II Substances</i>	This product, in compliance to the Act, does not contain any substances regulated as pollutants.
<i>Clean Water Act Priority or/and Toxic Pollutants</i>	This product, in compliance to the Act, does not contain any substances regulated as pollutants.
<i>DEA List I Chemicals (Precursor Chemicals) and List II Chemicals (Essential Chemicals)</i>	No component(s) listed; in compliance with the List.
<i>EPA List of Lists 313 Category Code:</i>	No component(s) listed; in compliance with the List.
<i>EPCRA 302 EHS TPQ</i>	No component(s) listed; in compliance with the List.
<i>CERCLA RQ</i>	No component(s) listed; in compliance with the List.
<i>EPCRA 313 TRI</i>	No component(s) listed; in compliance with the List.

Safety Data Sheet

Floor Guard Extreme – A- FLOORX-A
07.25.2023, Version 01.02
Page 8 of 10

RCRA Code No component(s) listed; in compliance with the List.

CAA 112 (r) TMP TQ No component(s) listed; in compliance with the List.

State Regulations

Massachusetts / Minnesota / New Jersey / Pennsylvania /
CAS 13463-67-7 Titanium Dioxide (airborne unbound particles of respirable size)
CAS 14464-46-1 CRISTOBALITE (dust)
CAS 14808-60-7 QUARTZ (dust)
CAS 15468-32-3 TRIDYMITE

New York / California
No component(s) listed; in compliance with the List.

CA Proposition 65:

WARNING! This product contains chemicals known to the State of California to cause cancer, reproductive harm, or birth defects.
CAS 13463-67-7 Titanium Dioxide (airborne unbound particles of respirable size)

16. OTHER INFORMATION

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H372 Causes damage to organs through prolonged or repeated exposure.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long-lasting effects.

LEGEND:

313 CATEGORY CODE	Emergency Planning and Community Right-to Know Act Section 313 Category Code
ADR	European Agreement concerning the carriage of Dangerous goods by Road
CAA 112 (r) RMP TQ	Risk Management Plan Threshold Quantity (Clean Air Act Section 112(R))
CAS NUMBER	Chemical Abstract Service Number
CE50	Effective concentration (required to induce a 50% effect)
CERCLA RQ	Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
CLP	EC Regulation 1272/2008
DEA	Drug Enforcement Administration
EmS	Emergency Schedule
EPA	US Environmental Protection Agency
EPCRA	Emergency Planning and Community Right-to-Know Act
EPCRA 302 EHS TPQ	Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
EPCRA 304 EHS RQ	Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
EPCRA 313 TRI	Toxics Release Inventory (Section 313 Category Code)
GHS	Globally Harmonized System of classification and labeling of chemicals
IATA DGR	International Air Transport Association Dangerous Goods Regulation
IC50	Immobilization Concentration 50%
IMDG	International Maritime Code for dangerous goods
IMO	International Maritime Organization
LC50	Lethal Concentration 50%
LD50	Lethal Dose 50%
OEL	Occupational Exposure Level
PEL	Predicted Exposure Level
RCRA Code	Resource Conservation and Recovery Act Code
REL	Recommended Exposure Limit
RID	Regulation concerning the international transport of dangerous goods by train
TLV	Threshold Limit Value
TLV CEILING	Concentration that should not be exceeded during any time of occupational exposure.
TSCA	Toxic Substances Control Act
TWA STEL	Short-term Exposure Limit
TWA	Time-weighted Average Exposure Limit
VOC	Volatile Organic Compounds
WHMIS	Workplace Hazardous Materials Information System

GENERAL BIBLIOGRAPHY:
- GHS rev. 3

Safety Data Sheet

Floor Guard Extreme – A- FLOORX-A
07.25.2023, Version 01.02
Page 9 of 10

- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

NOTE FOR USERS:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Purchasers must provide product users with adequate training on how to use chemical products.

ARMUS MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. ARMUS SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHT HELD BY OTHERS.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified: 02 / 03 / 08 / 11 / 15.

FLOOR GUARD EXTREME (Part B)

SAFETY DATA SHEET ACCORDING TO USA FEDERAL HAZCOM 012

1. IDENTIFICATION

1.1. Product Identifier

Code:

Product name

A-FLOORX-B

FLOOR GUARD EXTREME (Part B)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

*Self-leveling polyaspartic elastomeric floor coating with high resistance to weathering or UV; Part B hardener.
For professional use only.*

1.3. Details of the supplier of the safety data sheet

Name

Full address

Country

Armus LLC

137 Grand Street 3rd Floor

New York, NY 10013

United States

Tel. (+1) 917-957-5383

E-mail address of the competent person responsible for the Safety Data Sheet

bill@armussolutions.com

1.4. Emergency telephone number

For urgent inquiries refer to

Tel. (+1) 917-957-5383 United States

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment is given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Acute toxicity, category 3

Respiratory sensitization, category 1

Skin sensitization, category 1

Toxic if inhaled.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Hazard pictograms:



Signal words: **DANGER**

Hazard statements:

H331	Toxic if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.

Precautionary statements:

Prevention:

P261	Avoid breathing fume, mist, or spray.
P280	Wear protective gloves.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P284	Wear respiratory protection in case of inadequate ventilation.

Response:

P311	Call a POISON CONTROL CENTER / seek medical attention
P304+P340	IF INHALED: Move person to fresh air and keep comfortable
P302+P352	IF ON SKIN: Wash with plenty of water.
P363	Wash contaminated clothing before reuse.

Storage:

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Disposal:

P501	Dispose of contents or container according to local/national/international regulations
-------------	--

The mixture contains 99.90% mixed components of unknown acute inhalation toxicity.

2.2 Other hazards

Not applicable based on available information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1. Components

<i>Chemical Name</i>	<i>CAS-No</i>	<i>EC</i>	<i>INDEX</i>	<i>Conc. %</i>	<i>Classification</i>
HEXAMETHYLENE-DI-ISOCYANATE	822-06-0	212-485-8	315-011-00-1	0.1	Acute toxicity, category 3 H331, Eye irritation, category 2 H319, Skin irritation, category 2 H315, Specific target organ toxicity - single exposure, category 3 H335, Respiratory sensitization, category 1 H334, Skin sensitization, category 1 H317

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. FIRST-AID MEASURES

4.1. Description of first aid measures

GENERAL ADVICE:

Move out of work / application area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.

Safety Data Sheet

Floor Guard Extreme – A- FLOORX-B
07.25.2023, Version 01.02
Page 2 of 9

EYES:	Remove contact lenses. Keep eyes wide open while rinsing. In the case of contact with eyes, rinse immediately with plenty of water and seek medical attention. Continue rinsing eyes during transport to medical facility or for at least 30-60 minutes.
SKIN:	Take off contaminated clothing and shoes immediately. Wash immediately with plenty of water. If irritation persists, seek medical advice/attention. Wash contaminated clothing before using it again.
INHALATION:	Move to fresh air. In the event of breathing difficulties, seek medical advice/attention immediately.
INGESTION:	Seek medical advice / attention immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person, unless authorized by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product is unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Not applicable based on available information.

5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing equipment The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder, and water spray.

Unsuitable extinguishing equipment None in particular.

5.2. Special hazards arising from the substance or mixture

Specific hazards during fire fighting Do not breathe combustion products.

5.3. Advice for firefighters

General information Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health.
Always wear full fire prevention gear.
Collect extinguishing water to prevent it from draining into the sewer system.
Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

Special protective equipment for firefighters Normal firefighting clothing i.e., fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment, and emergency procedures

Block the leakage.

Wear suitable protective equipment (including personal protective equipment referred to under section 8 of the safety data sheet) to prevent any contamination of skin, eyes, and clothing.

These indications apply for both product users and those involved in emergency procedures.

6.2. Environmental precautions

The product must not enter the sewer system or come into contact with surface water or groundwater.

Safety Data Sheet

Floor Guard Extreme – A- FLOORX-B

07.25.2023, Version 01.02

Page 3 of 9

6.3. Methods and material for containment and cleaning up

Collect the leaked product.

Absorb spilled product with inert absorbent material.

Make sure the leakage site is well-aired.

Contaminated material should be disposed of in compliance with the provisions set forth in section 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet.

Do not eat, drink, or smoke during use.

Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

This product must not enter the sewer system or come into contact with surface water or groundwater.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container.

Store the containers sealed, in a well-ventilated place, away from direct sunlight.

7.3. Specific end use(s)

Refer to section 1.2

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

Regulatory References:

USA	NIOSH-REL	NIOSH PUBLICATION No. 2005-149, 3rd printing, 2007
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
	TLV-ACGIH	ACGIH 2020

HEXAMETHYLENE-DI-ISOCYANATE						
Threshold Limit Value						
Type	Country	TWA / 8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	Ppm	
NIOSH-REL	USA	0.035	0.005	0.14 (C)	0.02 (C)	
CAL/OSHA	USA	0.034	0.005			
TLV-ACGIH	---	0.034	0.005			

Legend:

(C) = CEILING

INHAL = Inhalable Fraction

RESP = Respirable Fraction

THORA = Thoracic Fraction

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well-aired through effective local ventilation. Personal protective equipment must comply with current regulations.

Hand Protection

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable.

The gloves' wear time depends on the duration and type of use.

Safety Data Sheet

Floor Guard Extreme – A- FLOORX-B

07.25.2023, Version 01.02

Page 4 of 9

<i>Skin Protection</i>	Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.
<i>Eye Protection</i>	Wear airtight protective goggles (OSHA 29 CFR 1910.133).
<i>Respiratory Protection</i>	<p>If the threshold value (e.g., TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134).</p> <p>In the presence of gases or vapors of various kinds and/or gases or vapors containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.</p> <p>Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.</p> <p>If the substance considered is odorless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.</p>
<i>Environmental Exposure Controls</i>	This product must not enter the sewer system or come into contact with surface water or groundwater.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Color	White
Odor	Light
pH	Not applicable
Density	1.12 g/cm ³
Flash point	> 201.2°F (94°C) @ 1,013 hPa
Initial boiling point	> 293°F (145°C)
Auto-ignition temperature	> 635°F (335°C) @ 1,013 hPa
Viscosity	> 1928 cP @ 68°F (20°C)
Vapor pressure	0.017 hPa @ 68°F (20°C)
Explosive properties	None
Oxidizing properties	None

10. STABILITY AND REACTIVITY

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Hexamethylene-di-isocyanate	Decomposes at: 491°F (255°C)
	Polymerizes at: > 392°F (200°C)

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

Hexamethylene-di-isocyanate	May form explosive mixtures with: alcohols, bases.
	May react violently with: alcohols, amines, strong bases, oxidizing agents, strong acids, water.

10.4. Conditions to avoid

None in particular. However, the usual precautions used for chemical products should be respected.

Safety Data Sheet

Floor Guard Extreme – A- FLOORX-B

07.25.2023, Version 01.02

Page 5 of 9

Hexamethylene-di-isocyanate

Avoid exposure to: high temperatures, moisture

10.5. Incompatible materials

Hexamethylene-di-isocyanate

Incompatible with: alcohols, carboxylic acids, amines, strong bases.

10.6. Hazardous decomposition products

Hexamethylene-di-isocyanate

May develop: nitric oxide, hydrogen cyanide.

11. TOXICOLOGICAL INFORMATION

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Not classified based on available information.

Information on likely routes of exposure

Not classified based on available information.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Not classified based on available information.

Interactive effects

Not classified based on available information.

Acute toxicity

Hexamethylene-di-isocyanate

LC50 (Inhalation (Rat)) 0.124 mg/liter
Exposure time: 4 h

Skin corrosion / irritation

Not classified based on available information.

Serious eye damage / irritation

Not classified based on available information.

Respiratory or skin sensitization

Sensitizing for the skin.

Sensitizing for the respiratory system.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT – single exposure

Not classified based on available information.

STOT – repeated exposure

Not classified based on available information.

Aspiration toxicity / hazard

Not classified based on available information.

Safety Data Sheet

Floor Guard Extreme – A- FLOORX-B

07.25.2023, Version 01.02

Page 6 of 9

12. ECOLOGICAL INFORMATION

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it has negative effects on aquatic environment.

12.1. Toxicity

None based on available information.

12.2. Persistence and degradability

Hexamethylene-di-isocyanate

Degradability NOT rapidly degradable

12.3. Bioaccumulative potential

Hexamethylene-di-isocyanate

Partition Co-efficient: N-octanol/water 3.2

BCF 3.2

12.4. Mobility in soil

None based on available information.

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any Persistent, Bioaccumulative and Toxic (PBT) or very Persistent and very Bio-accumulative (vPvB) in percentages greater than 0.1%.

13. DISPOSAL CONSIDERATIONS

Disposal methods

<i>Waste from residues</i>	Reuse, when possible. Unused product should be considered special non-hazardous waste. Disposal must be performed through an authorized waste management firm, in compliance with local, national, and international regulations.
<i>Contaminated Packaging</i>	Contaminated packaging must be recovered or disposed of in compliance with all waste management regulations.

14. TRANSPORTATION INFORMATION

This product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID) of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

15. REGULATORY INFORMATION

U.S. Federal Regulations

<i>TSCA</i>	All components of this product are listed on US Toxic Substances Control Act (TSCA) Inventory considered as "existing" chemical substances in U.S. commerce.	
<i>Clean Air Act Section 112(b)</i>	CAS 822-06-0	HEXAMETHYLENE-DI-ISOCYANATE
<i>Clean Air Act Sections 112(b), including 602 Class I Substances, 602 Class II Substances</i>	This product, in compliance to the Act, does not contain any substances regulated as pollutants.	
<i>Clean Water Act Priority</i>	This product, in compliance to the Act, does not contain any substances regulated	

Safety Data Sheet

Floor Guard Extreme – A- FLOORX-B

07.25.2023, Version 01.02

Page 7 of 9

<i>or/and Toxic Pollutants</i>	as pollutants.	
<i>DEA List I Chemicals (Precursor Chemicals) and List II Chemicals (Essential Chemicals)</i>	No component(s) listed; in compliance with the List.	
<i>EPA List of Lists 313 Category Code:</i>	CAS 822-06-0	HEXAMETHYLENE-DI-ISOCYANATE
<i>EPCRA 302 EHS TPQ</i>	No component(s) listed; in compliance with the List.	
<i>CERCLA RQ</i>	CAS 822-06-0	HEXAMETHYLENE-DI-ISOCYANATE
<i>EPCRA 313 TRI</i>	CAS 822-06-0	HEXAMETHYLENE-DI-ISOCYANATE
<i>RCRA Code</i>	No component(s) listed; in compliance with the List.	
<i>CAA 112 (r) TMP TQ</i>	No component(s) listed; in compliance with the List.	

State Regulations

Massachusetts / Minnesota / New Jersey / New York / California
CAS 822-06-0 HEXAMETHYLENE-DI-ISOCYANATE

Pennsylvania
No component(s) listed; in compliance with the List.

CA Proposition 65:

This product does not contain any substances known to the State of California to cause cancer, reproductive harm, or birth defects.

16. OTHER INFORMATION

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H331	Toxic if inhaled.
H318	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction

LEGEND:

313 CATEGORY CODE	Emergency Planning and Community Right-to Know Act Section 313 Category Code
ADR	European Agreement concerning the carriage of Dangerous goods by Road
CAA 112 (r) RMP TQ	Risk Management Plan Threshold Quantity (Clean Air Act Section 112(R))
CAS NUMBER	Chemical Abstract Service Number
CE50	Effective concentration (required to induce a 50% effect)
CERCLA RQ	Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
CLP	EC Regulation 1272/2008
DEA	Drug Enforcement Administration
EmS	Emergency Schedule
EPA	US Environmental Protection Agency
EPCRA	Emergency Planning and Community Right-to-Know Act
EPCRA 302 EHS TPQ	Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
EPCRA 304 EHS RQ	Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
EPCRA 313 TRI	Toxics Release Inventory (Section 313 Category Code)
GHS	Globally Harmonized System of classification and labeling of chemicals
IATA DGR	International Air Transport Association Dangerous Goods Regulation
IC50	Immobilization Concentration 50%
IMDG	International Maritime Code for dangerous goods
IMO	International Maritime Organization
LC50	Lethal Concentration 50%

Safety Data Sheet

Floor Guard Extreme – A- FLOORX-B
07.25.2023, Version 01.02
Page 8 of 9

LD50	Lethal Dose 50%
OEL	Occupational Exposure Level
PEL	Predicted Exposure Level
RCRA Code	Resource Conservation and Recovery Act Code
REL	Recommended Exposure Limit
RID	Regulation concerning the international transport of dangerous goods by train
TLV	Threshold Limit Value
TLV CEILING	Concentration that should not be exceeded during any time of occupational exposure.
TSCA	Toxic Substances Control Act
TWA STEL	Short-term Exposure Limit
TWA	Time-weighted Average Exposure Limit
VOC	Volatile Organic Compounds
WHMIS	Workplace Hazardous Materials Information System

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

NOTE FOR USERS:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Purchasers must provide product users with adequate training on how to use chemical products.

ARMUS MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. ARMUS SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHT HELD BY OTHERS.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified: 02 / 03 / 08 / 11 / 15.

Safety Data Sheet

Floor Guard Extreme – A- FLOORX-B

07.25.2023, Version 01.02

Page 9 of 9