



SMART, SUSTAINABLE
NANO-FORMULATED SOLUTIONS

HYDRO GUARD

Surface-applied water-repellent treatment for the protection of concrete, cement stucco, mortar, brick, and artificial & natural stone.



RETAINS SURFACE APPEARANCE

Hydro Guard does not add a sheen or gloss post-application. Your treated surface will retain its natural color and low gloss.

MAINTAINS BREATHABILITY

Unlike traditional sealants or coatings, Hydro Guard creates a water-repelling near-surface zone without sealing substrate pores. If there is water or leakage behind the Hydro Guard-treated surface, water can evaporate through those open pores, permitting drying and preventing swelling and cracking.







EASY TO APPLY AND CLEAN

After applying Hydro Guard, it starts working 24 hours after its dry! Protection comes from the inside out, making your surfaces water-resistant! Protect your horizontal and vertical surfaces from water ingress and water damage! If your site is located in an area with weather, protect surfaces from the damage of a freeze/thaw cycle!







RESISTANT TO UV RADIATION

Hydro Guard's is a non-toxic and water-borne formulation and is resistant to UV radiation, thus preventing surfaces from yellowing over time.

FEATURES

-  **WATER-REPELLENT BARRIER**
-  **RETAINS BREATHABILITY**
-  **PREVENTS MOLD GROWTH**
-  **RESISTANT TO UV RADIATION**
-  **RETAINS NATURAL APPEARANCE**
-  **SAVES ON CLEANING COSTS**

SUBSTRATES

-  **CONCRETE**
-  **BRICK & MORTAR**
-  **LIMESTONE**
-  **CEMENT / STUCCO**
-  **GRANITE**
-  **ARTIFICIAL & NATURAL STONE**

ESTIMATED COVERAGE

- **1 GALLON** ~300-350 SQ. FT. (7.3-8.5 SQUARE METERS / LITER)





SMART, SUSTAINABLE
NANO-FORMULATED SOLUTIONS



HYDRO GUARD

SEE WHY THE PROS CHOOSE HYDRO GUARD.
BETTER PERFORMANCE.
BETTER PROTECTION.
BETTER FINISH.
BETTER FOR THE ENVIRONMENT.

APPLICATION & POST-APPLICATION CARE

With the proper care, Hydro Pro can provide long-term protection for your vessel. Application is simple and you can even do it yourself. Check out our website for our Application Guide for different substrates.

On new building surfaces and installed repair materials, ensure the substrate is fully cured prior to application.

We recommend using a sprayer to apply Hydro Guard in a single-saturating application. Hydro Guard is ready to use right out of the bottle, without dilution. Just load your pump sprayer immediately after shaking, and you're ready to go!

Contact us with questions about application, your substrate, or project. We've got you covered and we're here to help!

HYDRO GUARD CAN HELP PREVENT PROBLEMS!

MOLD & ORGANIC GROWTH



Applying Hydro Guard creates a water-repellent barrier on treated surfaces. Without water, mold and organic growth cannot develop and take hold of the substrate.

WATER-DAMAGED WALLS



Hydro Guard prevents water-ingress and stabilizes materials, keeping building surfaces protected and cleaner longer. Prevent water damage from the freeze/thaw cycle!

DETERIORATING MORTAR JOINTS



Water infiltration can accelerate the deterioration of mortar joints, causing mortar to crack or separate from the blocks, creating a risk for leaks and water ingress. Hydro Guard applies easily and protects mortar as well!

YOU'VE GOT TO SEE IT TO BELIEVE IT

UNTREATED SPLIT-FACE BLOCK



HYDRO GUARD-PROTECTED SPLIT-FACE BLOCK



MAIL: INFO@ARMUSSOLUTIONS.COM

WEB: ARMUSSOLUTIONS.COM