

METAL GUARD

FOR ALL METAL SURFACES


A 2-part nano-formulated high-gloss metal protectant that cleans easily and prevents future rust and corrosion.



FEATURES

-  ANTI-GRAFFITI & STAINS
-  EASY TO CLEAN
-  HIGH-GLOSS FINISH
-  CORROSION PROTECTION

SUBSTRATES



PREVENTATIVE MAINTENANCE



THE NANO-SCIENCE

Metal Pro is a graffiti and stain silicone-epoxy protectant. Graffiti can be cleaned easily with one pass using a damp cloth within 48 hours of staining. Power washing is recommended for longer-setting stains. Without PFOS/ PFAS or Teflon, it is both environmentally friendly, and provides anti-corrosion protection.

APPLICATION

SURFACE PREP

- Power wash and dry hulls. Wipe down all hulls with lint-free cloth and Xylol Xylene thinner.
- Allow surfaces to dry completely.
- Tape off all sections that you do not want protected.
- Be sure to leave welds and seams untaped so Hull Pro can protect them



APPLICATION

- Completely mix Part A (Base) & Part B (Hardener) together
- Stir well for a minimum of 2 minutes at low RPM using a paint mixer.
- Allow mixed components to sit for 10 minutes prior to application.
- Roll on to all surfaces of the hull. Any sections that cannot be reached by roller should have Metal Guard applied by foam brush
- Smooth any drips or imperfections by tipping with foam brush.
- After applying to all surfaces, be sure to visually inspect all areas to correct for any sagging by tipping with foam brush
- Allow to dry. Full cure in 24 hours, depending on temperature and humidity.
- Vessel immersion is allowed 48 hours post-dry.*
- * Check that coating is not tacky prior to immersion in water.

ESTIMATED CONSUMPTION

- Up to 431 sq.ft. per gallon, dependent on properties of surface.

SCAN QR CODE TO REAL FULL TECHNICAL DATA SHEET BEFORE APPLYING.

SAFETY AND STORAGE

WARNING:

- Flammable. Keep away from heat.
- Harmful if swallowed / inhaled.
- Causes skin/eye irritation.
- May cause allergic reaction.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Contaminated work clothing/gear should not be allowed out of the workspace.
- Avoid breathing dust / fumes / vapors. Use in a well-ventilated area and wear proper protective gear and clothing prior to application.



STORAGE & DISPOSAL

- Store indoors in a closed container. Storage temperature should be between +50°F to 95°F (+10°C to +35°C).
- Disposal of container and material safely according to local laws and regulations.

SCAN QR CODE TO READ FULL SAFETY DATA SHEET BEFORE APPLYING.