

Revision nr. 1 Dated 01/20/2022 First compilation Printed on 01/20/2022 Page n 1/10

Thermal Guard - Interior

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

1. Identification	
1.1. Product identifier Code: Product name	Armus_GA_020920-019 Thermal Guard Interior
	s of the substance or mixture and uses advised against insulating acrylic paint for interior walls & ceilings
1.3. Details of the supplier of	of the safety data sheet
Name	Armus LLC
Full address	137 Grand Street 3rd floor NY
District and Country	NY 10013
	United States
	Tel. (+1) 9179575383
e-mail address of the comp responsible for the Safety D	
. ,	
1.4. Emergency telephone	number
For urgent inquiries refer to	Tel. (+1) 9179575383 United States
2. Hazards identification	
2.1. Classification of the sul	ostance or mixture
The product is not classified CFR 1910.1200).	d as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29
Hazard pictograms:	
Signal words:	
Hazard statements:	
Precautionary statements:	
Prevention:	
Response: Storage:	
Disposal:	
P501	Dispose of contents or container according to local/national/international regulations



Revision nr. 1 Dated 01/20/2022 First compilation Printed on 01/20/2022

Page n 2/10

Thermal Guard - Interior

2.2 Other hazards

Information not available.

3. Composition / information on ingredients

3.1. Mixtures

Contains:

This product does not contain substances classified as being hazardous to human health or the environment pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200).

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again. INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorized by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder, and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.



Revision nr. 1 Dated 01/20/2022 First compilation Printed on 01/20/2022 Page n 3/10

Thermal Guard - Interior

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal firefighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment, and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well-ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls / personal protection

8.1. Control parameters

Information not available.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).



Revision nr. 1

Dated 01/20/2022

First compilation

Printed on 01/20/2022

Page n 4/10

Thermal Guard - Interior

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose limit of use will be defined by the manufacturer (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapors of various kinds and/or gases or vapors containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odorless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Pasty Liquid
Color	White
Odor	Mild
Odor threshold	Not available
рН	8.7 ± 0.5
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	> 93°C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapor pressure	Not available
Vapor density	Not available
Relative density	1.10 ± 0.05 kg/L
Solubility	Not available

Revision nr. 1 Dated 01/20/2022 First compilation Printed on 01/20/2022 Page n 5/10

Thermal Guard - Interior

Partition coefficient: n-octanol/waterNAuto-ignition temperatureNDecomposition temperatureNViscosity13Explosive propertiesNOxidizing propertiesN

Not available Not available 130 KU Not available Not available

9.2. Other information

Information not available.

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However, the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available.

10.6. Hazardous decomposition products

Information not available.

11. Toxicological information

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information Information not available

Information on likely routes of exposure 2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion, and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapor pressure of the substance.

Interactive effects Information not available



Revision nr. 1 Dated 01/20/2022 First compilation Printed on 01/20/2022 Page n 6/10

Thermal Guard - Interior

<u>ACUTE TOXICITY</u> Does not meet the classification criteria for this hazard class.

<u>SKIN CORROSION / IRRITATION</u> Does not meet the classification criteria for this hazard class.

<u>SERIOUS EYE DAMAGE / IRRITATION</u> Does not meet the classification criteria for this hazard class.

<u>RESPIRATORY OR SKIN SENSITISATION</u> Contains: May produce an allergic reaction.

<u>GERM CELL MUTAGENICITY</u> Does not meet the classification criteria for this hazard class.

<u>CARCINOGENICITY</u> Does not meet the classification criteria for this hazard class.

<u>REPRODUCTIVE TOXICITY</u> Does not meet the classification criteria for this hazard class.

<u>STOT - SINGLE EXPOSURE</u> Does not meet the classification criteria for this hazard class.

<u>STOT - REPEATED EXPOSURE</u>

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class.

12. Ecological information

12.1. Toxicity Information not available.

12.2. Persistence and degradability

Information not available.

12.3. Bioaccumulative potential

Information not available.

12.4. Mobility in soil

Information not available.

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0.1%.

12.6. Other adverse effects

Information not available



Revision nr. 1 Dated 01/20/2022 First compilation Printed on 01/20/2022 Page n 7/10

Thermal Guard - Interior

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste. Disposal must be performed through an authorized waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number Not applicable. 14.2. UN proper shipping name Not applicable. 14.3. Transport hazard class(es) Not applicable. 14.4. Packing group Not applicable. 14.5. Environmental hazards Not applicable. 14.6. Special precautions for user Not applicable. 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code Information not relevant.

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixtureU.S. Federal RegulationsISCA:All components are listed on TSCA Inventory.

<u>Clean Air Act Section 112(b):</u> No component(s) listed.

<u>Clean Air Act Section 602 Class I Substances:</u> No component(s) listed. **Thermal Guard - Interior**

Revision nr. 1

Dated 01/20/2022

First compilation

Printed on 01/20/2022

Page n 8/10

<u>Clean Air Act Section 602 Class II Substances:</u> No component(s) listed.

<u>Clean Water Act</u> <u>Priority Pollutants:</u> No component(s) listed.

<u>Clean Water Act</u> <u>Toxic Pollutants:</u> No component(s) listed.

DEA List I Chemicals (Precursor Chemicals): No component(s) listed.

DEA List II Chemicals (Essential Chemicals): No component(s) listed.

EPA List of Lists: 313 Category Code: No component(s) listed.

EPCRA 302 EHS TPQ: No component(s) listed.

EPCRA 304 EHS RQ: No component(s) listed.

CERCLA RQ: No component(s) listed.

EPCRA 313 TRI: No component(s) listed.

RCRA Code: No component(s) listed.

CAA 112 (r) RMP TQ: No component(s) listed.

State Regulations

Massachusetts: 124-68-5

2-AMINO-2-METHYLPROPANOL

Minnesota: 57-55-6

1.2 - PROPANEDIOL

New Jersey: 57-55-6 124-68-5

1.2 – PROPANEDIOL 2-AMINO-2-METHYLPROPANOL



Revision nr. 1 Dated 01/20/2022 First compilation Printed on 01/20/2022 Page n 9/10

Thermal Guard - Interior

New York:

No component(s) listed.

Pennsylvania:

57-55-6 124-68-5 1.2 – PROPANEDIOL 2-AMINO-2-METHYLPROPANOL

California:

No component(s) listed.

Proposition 65:

This product does not contain any substances known to the State of California to cause cancer, reproductive harm, or birth defects.

International Regulations

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012: None

Substances subject to the Rotterdam Convention: None

<u>Substances subject to the Stockholm Convention:</u> None

16. Other information

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level



Revision nr. 1 Dated 01/20/2022 First compilation Printed on 01/20/2022 Page n 10/10

Thermal Guard - Interior

- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.

- OSHA website

- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.